

FLEXIBLE SYSTEM SOLUTION

Product Family	Capacity kBtu/h	7.5	9.5	12.3	15.3	19.1	24.2	27.3	30.7	38.2	47.7	77.1	95.5
	Capacity kW	2.2	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2	14.0	22.6	28.0
Slim Low Static Pressure Duct 185mm (0/20Pa)			X	X	X	X	X						
Low Static Pressure Duct (0/20Pa)		X	X	X	X	X	X						
Medium Static Pressure Duct (50/96Pa)						X	X	X					
Medium Static Pressure Duct (80/120Pa)									X	X	X		
High Static Pressure Duct (100/196Pa)						X	X	X	X	X	X		
												X	X
Two Way Cassette			X	X	X	X							
Four Way Compact Cassette (700x700)			X	X	X								
Four Way Cassette (950x950)						X	X	X	X	X	X		
High Wall		X	X	X	X	X	X						
Console		X	X	X		X							
Floor Ceiling			X	X	X	X	X	X	X	X	X		
Fresh Air Unit											X		
												X	X
Heat Recovery Ventilator (CMH/CFM)		150 /88	260 /153	800 /471	1000 /588								

Flexible Combinations

- Up to 64 indoor units can be connected to a single refrigerant cycle
- Total indoor unit capacity can be 50-130% of outdoor units

