

CONSOLE

Features

- Compact design & small footprint
- Built-in EEV
- Quiet operation
- Easy installation and maintenance
- Air filter easily removed and cleaned
- Air discharge through Top (Cooling) or Bottom (Heating)
- Without built-in high head drain pump, optional external drain pump not available
- Wireless controller is standard



Specification

Model Name		YV5VXH022WAR--GX	YV5VXH028WAR--GX	YV5VXH036WAR--GX	YV5VXH056WAR--GX	
Power Supply	Ph-V-Hz	1Ph/220~230V/50-60Hz	1Ph/220~230V/50-60Hz	1Ph/220~230V/50-60Hz	1Ph/220~230V/50-60Hz	
Nominal Capacity						
Cooling	Capacity	kW	2.2	2.8	3.6	5
	Input	W	100	100	100	100
	Current	A	0.44	0.44	0.44	0.44
Heating	Capacity	kW	2.5	3.2	4	6
	Input	W	100	100	100	100
	Current	A	0.44	0.44	0.44	0.44
Motor						
Input	W	55+33	55+33	55+33	55+33	
Capacitor	µF	1.2µF/450V	1.2µF/450V	1.2µF/450V	1.2µF/450V	
Speed (H/M/L)	rpm	900/850/800 (Up) 850/800/750 (Down)	900/850/800 (Up) 850/800/750 (Down)	1000/925/850(Up) 950/875/800 (Down)	1250/1000/950 (Up) 1200/950/900 (Down)	
Performance						
Indoor Noise Level (H/M/L)	dB(A)	43/39/36	43/39/36	43/39/36	48/46/42	
External Static Pressure	Pa	/	/	/	/	
Indoor Air Flow (H/M/L)	m3/h	460/370/280	460/370/280	520/430/340	580/490/400	
Piping Size	Liquid/Gas	mm	ø6.35/ø12.7	ø6.35/ø12.7	ø6.35/ø12.7	
Containerization						
Indoor unit	Dimension (WxHxD)	mm	720x640x255	720x640x255	720x640x255	720x640x255
	Packing (WxHxD)	mm	784x719x305	784x719x305	784x719x305	784x719x305
	Net/Gross weight	kg	18/20	18/20	18/20	18/20
Qty per 20'/40'/40'HQ	Pieces	168/360/360	168/360/360	168/360/360	168/360/360	

Rating Conditions(AHRI1230):

	Outdoor Temperature	Indoor Temperature
Cooling:	35°DB/23.9°WB	26.7°DB/19.4°WB
Heating:	8.3°DB/6.1°WB	21.1°DB /15.6°WB