

## TWO-WAY CASSETTE

### Features

- Stylish design
  - Seamless integration with any interior decor
- 220mm height
- Quiet operation
- Easy installation
- Built-in water pump with maximum 700mm head
- Easy cleaning and maintenance with flat type suction grille
- Wired controller is standard



### Specification

Model Name			YV8VXH028WAR--GX	YV8VXH036WAR--GX	YV8VXH045WAR--GX	YV8VXH056WAR--GX
Power Supply		Ph-V-Hz	1Ph/220~230V/50~60Hz	1Ph/220~230V/50~60Hz	1Ph/220~230V/50~60Hz	1Ph/220~230V/50~60Hz
Nominal Capacity						
Cooling	Capacity	kW	2.8	3.6	4.5	5.6
	Input	W	90	90	110	110
	Current	A	0.5	0.5	0.62	0.62
Heating	Capacity	kW	3.2	4	5	6.3
	Input	W	90	90	110	110
	Current	A	0.5	0.5	0.62	0.62
Motor						
Input	W		70	70	70	70
Capacitor	µF		3 µF/450V	3µF/450V	3µF/450V	3µF/450V
Speed (H/M/L)	rpm		670/530/440	670/530/440	670/530/440	670/530/440
Performance						
Indoor Noise Level (H/M/L)	dB(A)		42/37/33	42/37/33	44/39/34	44/39/34
External Static Pressure	Pa		/	/	/	/
Indoor Air Flow (H/M/L)	m3/h		840/700/550	840/700/550	840/700/550	840/700/550
Piping Size	Liquid/Gas	mm	ø6.35/ø9.52	ø6.35/ø12.7	ø6.35/ø12.7	ø6.35/ø12.7
Containerization						
Indoor unit	Dimension (WxHxD)	mm	817x220x620(Cabinet) 1055x8x680(Panel)	817x220x620(Cabinet) 1055x8x680(Panel)	817x220x620(Cabinet) 1055x8x680(Panel)	817x220x620(Cabinet) 1055x8x680(Panel)
	Packing (WxHxD)	mm	1015x278x695(Cabinet) 1110x161x720(Panel)	1015x278x695(Cabinet) 1110x161x720(Panel)	1015x278x695(Cabinet) 1110x161x720(Panel)	1015x278x695(Cabinet) 1110x161x720(Panel)
	Net/Gross weight	kg	21+7/23+8	21+7/23+8	21+7/23+8	21+7/23+8
Qty per 20'/40'/40'HQ	Pieces		84/168/192	84/168/192	84/168/192	84/168/192

### Rating Conditions(AHRI1230):

	Outdoor Temperature	Indoor Temperature
Cooling:	35°DB/23.9°WB	26.7°DB/19.4°WB
Heating:	8.3°DB/6.1°WB	21.1°DB /15.6°WB